



## MTM Touch Monitor Box Module



## **FEATURES**

- Modularized Design for different application needs and minimal system down time during maintenance
- Solid and rugged System Construction withstands punishments from all environments
- Supports Multiple Output I/O ports
- 4 Different mounting methods designed in for ultimate application flexibility

## **APPLICATIONS**

- Industrial Automation
- Home Automation
- Digital Signage
- In-Vehicle System









System Box Module				
	USB x 1 (For Touch)			
	VGA x 1			
I/O	HDMI 1.4a x 1			
	DisplayPort 1.2 x 1			
	Line Out x 1			
Power Requirement	DC Jack, +24V			
Mechanical				
Construction	Heavy-duty steel chassis (Black)			
Operation Temp.	32°F ~ 104°F (0°C ~ 40°C) with Ambient Air			
Storage Temp.	-22°F ~ 175°F (-30°C ~ 80°C)			
Relative Humidity	10~90% @40°C, Non-condensing			
Backlight Lifetime	50,000hrs / LED			
Vibration	5-17Hz, 0.1" double amplitude peak to peak, 1.5G acceleration peak to peak			
Shock	10G acceleration peak to peak (11ms)			
Rating	IP 65 compliant front bezel			
Qualification	Formal certification CE/FCC Class B			
Mounting	Panel/ VESA 100/ Wall/ Clamp Type			
Dimension	128 x 25.3 x 268 mm			
Packing Dimension	580 x 180 x 420 mm			
System Weight(N.W.)	0.85 KG			
Weight with Packing(G.W.)	2.05 KG			
Optional Order				
Power	AC to PWR Terminal Connector			

## **Modularized Industrial Panel PC Display Module**

10.4"	12.1"	15"	17"	21.5"	23.5"	27"